

CP-S Conductor Pipe Slip:

Description	Casing Size (OD, inches)			
	24	26	30	36
P/N, Slip Complete w/Circular Buttons	5341	5342	5343	5344
Weight Complete with Inserts	125 Kg.	134 Kg.	145 Kg.	164 Kg.
Total Number of Segments	13 No.	14 No.	16 No.	18 No.
Total Number of Hinge Pins	24 No.	26 No.	30 No.	34 No.

Part List of Casing Slips:

Description	P/N
Segment - Right End	5316
Segment - Left End	5317
Segment - Intermediate	5318
Hinge Pin w/Cotter Pin	5319
Handle Pin w/Washer & Cotter Pin	5320
Handle for Right & Left End Segment	5321
Handle for Intermediate Segments	5322
Retaining Screw w/Lock Washer	5323

FLEXIBLE HANDLES

1. Flexible Handles can be easily fitted onto slips without requiring any modification.
2. Flexible Handles offer increased safety during use and are more durable.
3. They help reduce the likelihood of bending and breaking.
4. Flexible Handles minimize the risk of injury to the crew.



Flexible Handles
Figure No. 31

Part No. for Circular Buttons:

Type	Slips	Circular Buttons	
	Casing Sizes (Inches)	P/N	Qty. Per Unit
CMS-XL	5	5221-132	132 No.
	5.1/2	5222-132	132 No.
	6.5/8	5228-144	144 No.
	7	5219-144	144 No.
	7.5/8	5230-144	144 No.
	8.5/8	5230-156	156 No.
	9	5229-168	168 No.
	9.5/8	5230-168	168 No.
	9.7/8 & 10	5230-168	168 No.
	10.3/4	5230-180	180 No.
EXTRA	11.3/4	5227-204	204 No.
	12.3/4	5231-216	216 No.
LONG	13.3/8	5230-216	216 No.
	14	5228-228	228 No.
	16	5231-252	252 No.
	16.3/4	5231-264	264 No.
	18	5228-300	300 No.
	18.5/8	5226-300	300 No.
	20	5231-312	312 No.
	22	5230-336	336 No.
	24	5231-360	360 No.
	26	5231-396	396 No.
28	5228-432	432 No.	
30	5231-444	444 No.	

Description	Handle Part No.		
	For Rotary Slips	For Drill Collar Slips	For Casing Slips
Handle for Segment-Right End	5110F	5217F (R)	5321F (R)
Handle for Segment-Left End	5112F	5217F (L)	5321F (L)
Handle for Segment-Intermediate	5111F	5218F	5322F